


BERRI 74600 HORIZONTAL


PROJECT PROJÉT

SPEC TYPE

NOTES



FINISH FINI




BLKE WHE SGO

FAMILY FAMILLE




ANGULAR 3D HEXAGONAL




HORIZONTAL VERTICAL SQUARE & RECTANGLE

MOUNTING OPTION OPTION DE MONTAGE



MOUNTING CABLE OPTION OPTION DE MONTAGE DE CÂBLE



PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT




ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE		CODE
MODEL MODÈLE		
74600-L02-36	BERRI HORIZONTAL 2 HEADS 36"	
74600-L02-48	BERRI HORIZONTAL 2 HEADS 48"	
74600-L03	BERRI HORIZONTAL 3 HEADS	
74600-L04	BERRI HORIZONTAL 4 HEADS	
74600-L05	BERRI HORIZONTAL 5 HEADS	
74600-L06	BERRI HORIZONTAL 6 HEADS	
74600-L08	BERRI HORIZONTAL 8 HEADS	
LIGHT SOURCE SOURCE LUMINEUSE		
LED	REGULAR OUTPUT	
LED.HO	HIGH OUTPUT	
COLOR TEMPERATURE TEMPÉRATURE DE COULEUR		
27*	2700K	
30	3000K	
35	3500K	
40	4000K	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE TUNABLE WHITE ALSO AVAILABLE, SEE TUNABLE WHITE SPEC SHEET.		
COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)		
80	80+ CRI	
90*	90+ CRI	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
VOLTAGE VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
CONTROL OPTION OPTION DE GRADATION		
DV	0-10V DIMMING (120V-227V)	
DP	PHASE DIMMING (120V ONLY)	
NLTAIR2*	NLIGHT AIR CONTROL GEN 2	
NLIGHT*	NLIGHT WIRED CONTROL	
* REQUIRES RC2 CANOPY * EMERGENCY BATTERY NOT AVAILABLE WITH NLIGHT OPTIONS REFER TO NLIGHT GUIDE AND INSTALLATION SHEET FOR ALL REQUIREMENTS.		
EMERGENCY BATTERY BATTERIE D'URGENCE		
FOR 120-277V ONLY. EM DRIVER BOX INCLUDED, INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.		
EMB*	EMERGENCY BATTERY FOR REMOTE BOX	
* 3981EA ACCESSORY IS REQUIRED FOR THIS OPTION * REQUIRES RC1 CANOPY		
CABLE CÂBLE		AC
AC	AIRCRAFT MOUNTING & POWER CORD, FIELD ADJUSTABLE	
CABLE LENGTH LONGUEUR DE CÂBLE		
60	60" AIRCRAFT CABLE (STD LENGTH)	
**	CUSTOM AIRCRAFT CABLE LENGTH (PLEASE SPECIFY) FOR OVERALL LENGTH, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
MOUNTING OPTION OPTION DE MONTAGE		
RC1	ROUND CANOPY / PAVILLON ROND	
RC2	SCREWLESS 1.35" CANOPY (2473F)	
RC3*	NLIGHT SCREWLESS 1.30" CANOPY (2474H) OFFSET SLIM PLATE ON REMOTE JBOX (2401A)	
* ONLY AVAILABLE WITH ROC CANOPY POSITION * NON IC RATED FOR HO		
MOUNTING CABLE OPTION OPTION DE MONTAGE DE CÂBLE		
RC	CANOPY WITH AIRCRAFT CABLE	
ROC	CANOPY OFFSET TO AIRCRAFT CABLE	
CANOPY FINISH FINI PAVILLON		
WHE	WHITE FINE TEXTURE	
BLKE	BLACK FINE TEXTURE	
POWER CORD & GRIPPER FINISH FINI CÂBLE D'ALIMENTATION ET ATTACHES		
WH	WHITE POWER CORD & WHITE FINE TEXTURED GRIPPER	
BLK	BLACK POWER CORD & BLACK FINE TEXTURED GRIPPER	
TUBE FINISH FINI TUBE		
WHE	WHITE FINE TEXTURE	
BLKE	BLACK FINE TEXTURE	
SGO	SOFT GOLD	
RAL*	PLEASE SPECIFY RAL CODE	
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE		
DIFFUSER FINISH FINI DIFFUSEUR		WH
WH	WHITE	
ACCESSORY EMERGENCY BATTERY ACCESSORY EMERGENCY BATTERY		
3981EA	ELECTRICAL BOX FOR EMB EMERGENCY BATTERY	

BERRI 74600 HORIZONTAL TUNABLE WHITE


PROJECT PROJCT

SPEC TYPE


NOTES




FINISH FINI




FAMILY FAMILLE



MOUNTING OPTION OPTION DE MONTAGE



MOUNTING CABLE OPTION OPTION DE MONTAGE DE CÂBLE



ORDERING SPECIFICATION SPÉCIFICATION DE COMMANDE		CODE
MODEL MODÈLE		
74600-L02-36	BERRI HORIZONTAL 2 HEADS 36"	
74600-L02-48	BERRI HORIZONTAL 2 HEADS 48"	
74600-L03	BERRI HORIZONTAL 3 HEADS	
74600-L04	BERRI HORIZONTAL 4 HEADS	
74600-L05	BERRI HORIZONTAL 5 HEADS	
74600-L06	BERRI HORIZONTAL 6 HEADS	
74600-L08	BERRI HORIZONTAL 8 HEADS	
LIGHT SOURCE SOURCE LUMINEUSE		TW
LED	REGULAR OUTPUT	
LED.HO*	HIGH OUTPUT	
	* NOT AVAILABLE WITH 74600-L08	
COLOR TEMPERATURE TEMPÉRATURE DE COULEUR		80
TW*	TUNABLE WHITE (2700K TO 5000K)	
	* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
COLOR RENDERING INDEX (CRI) INDICE DE RENDU DE COULEUR (IRC)		
80	80+ CRI	
VOLTAGE VOLTAGE		
120V	120 VOLT	
277V	277 VOLT	
CONTROL OPTION OPTION DE GRADATION		
DV	DUAL 0-10V DIMMING	
NLT*	NIGHT NTUNE CONTROL	
	* REFER TO NLIGHT GUIDE AND INSTALLATION SHEET FOR ALL REQUIREMENTS.	
CABLE CÂBLE		AC
AC	AIRCRAFT MOUNTING & POWER CORD, FIELD ADJUSTABLE	
CABLE LENGTH LONGUEUR DE CÂBLE		
60	60" AIRCRAFT CABLE (STD LENGTH)	
**	CUSTOM AIRCRAFT CABLE LENGTH (PLEASE SPECIFY)	
	FOR OVERALL LENGTH, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
MOUNTING OPTION OPTION DE MONTAGE		
	ROUND CANOPY / PAVILLON ROND	
RC3*	OFFSET SLIM PLATE ON REMOTE JBOX (2401A)	
RC4	TUNABLE WHITE SCREWLESS 1.87" CANOPY (2475I)	
	* ONLY AVAILABLE WITH ROC CANOPY POSITION	
	* NOT AVAILABLE WITH NTUNE OPTION	
MOUNTING CABLE OPTION OPTION DE MONTAGE DE CÂBLE		
RC	CANOPY WITH AIRCRAFT CABLE	
ROC	CANOPY OFFSET TO AIRCRAFT CABLE	
CANOPY FINISH FINI PAVILLON		
WHE	WHITE FINE TEXTURE	
BLKE	BLACK FINE TEXTURE	
POWER CORD & GRIPPER FINISH FINI CÂBLE D'ALIMENTATION ET ATTACHES		
WH	WHITE POWER CORD & WHITE FINE TEXTURED GRIPPER	
BLK	BLACK POWER CORD & BLACK FINE TEXTURED GRIPPER	
TUBE FINISH FINI TUBE		
WHE	WHITE FINE TEXTURE	
BLKE	BLACK FINE TEXTURE	
SGO	SOFT GOLD	
RAL*	PLEASE SPECIFY RAL CODE	
	* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE	
DIFFUSER FINISH FINI DIFFUSEUR		WH
WH	WHITE	


PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT




BERRI 74600-HORIZONTAL

CONFIGURATIONS


L02-36
BERRI HORIZONTAL 2 HEADS 36"




L02-48
BERRI HORIZONTAL 2 HEADS 48"




L03
BERRI HORIZONTAL 3 HEADS




L04
BERRI HORIZONTAL 4 HEADS




L05
BERRI HORIZONTAL 5 HEADS



L06
BERRI HORIZONTAL 6 HEADS



L08
BERRI HORIZONTAL 8 HEADS



BERRI 74600

INSTALLATION WITHOUT CONSTRAINT

CANOPY OPTIONS

RC1
SCREWLESS
1.35" CANOPY

RC2
NIGHT SCREWLESS
1.30" CANOPY

RC3
OFFSET SLIM PLATE
ON REMOTE JBOX

RC4
TUNABLE WHITE
SCREWLESS 1.87" CANOPY

HANGING POSSIBILITIES
Suspension cables can be placed freely along the tube and length can be easily adjusted for multiple hanging possibilities.

ROTOMOLDED SHADE
Translucent white diffuser made of impact-resistant rotomolded polyethylene.

EFFORTLESS ASSEMBLY
Large Berri configurations are shipped in subassembly and are quickly joined with the tightening screws placed at each end of the tubes.

EASY CONNECTIONS
Electrically connect Berri modules or subassembly using quick-connect wire connectors.


VARIOUS COLORS OPTIONS
Extruded aluminum tubing, offered in 3 finishes : fine textured white, fine textured black and soft gold.

DIFFUSED LIGHT
Two LED strips in the center of the diffuser provide diffused and uniform light.

PRODUCT SPECIFICATION	PER HEAD			
PERFORMANCE	REG	HO	TUNABLE WHITE REG	TUNABLE WHITE HO
SYSTEM WATTAGE	4.4W	8.1W	4.4W	8W
DELIVERED LUMENS (4000K)	671 LM	1143 LM	568 LM	952 LM
EFFICACY	153 LM/W	142 LM/W	129 LM/W	119 LM/W
OTHER INFORMATION				
AVG. WEIGHT PER HEAD	1.5LBS / 0.7KG	1.5LBS / 0.7KG	1.5LBS / 0.7KG	1.5LBS / 0.7KG
* Refer to installation sheets for weight per configuration.				
L70 (LUMEN MAINTENANCE)	60,000	60,000	54,700	54,700
WELL & LEED STANDARD REQUIREMENTS				
MAX. LUMINANCE 450-900 OF NADIR	1150 CD/M² (AT HO)			
CRI ≥90 LED BOARDS	YES (R9 = 58.8 WITH 4000K)			
FLICKERING TOLERANCE	LOW FLICKER, COMPLIANT TO CALIFORNIA TITLE 24			

EFFICACY MULTIPLIERS

CRI	CCT	FACTOR	TW FACTOR
80+	5000K	-	0.93
80+	4000K	1.00	1.00
80+	3500K	0.98	0.99
80+	3000K	0.94	0.98
80+	2700K	0.91	0.91
90+	4000K	0.88	-
90+	3500K	0.85	-
90+	3000K	0.81	-
90+	2700K	0.77	-



Visit our website for warranty terms and conditions.

5 years warranty

BERRI 74600

INSTALLATION SANS CONTRAINTE

JUSQU'À 60° PLACEMENT LIBRE LES TUBES PEUVENT S'AJUSTER À 360° LES COUDES PEUVENT ÊTRE CONFIGURÉS À 360°

OPTIONS DE CANOPY

RC1 PAVILLON AIMANTÉ 1.35"
RC2 PAVILLON AIMANTÉ NLIGHT 1.30"
RC3 BOÎTE DE JONCTION À DISTANCE & PLAQUE
RC4 PAVILLON AIMANTÉ TUNABLE WHITE 1.87"

RC
PAVILLON AVEC CÂBLE EN ACIER

ROC
PAVILLON SÉPARÉ DU CÂBLE EN ACIER

POSSIBILITÉS DE SUSPENSION
Les câbles de suspension peuvent être placés librement le long du tube et la longueur peut être facilement ajustée pour de multiples possibilités d'installation.

ABAT-JOUR ROTOMOULÉ
Diffuseur blanc translucide en polyéthylène rotomoulé résistant aux chocs

ASSEMBLAGE SANS EFFORT
Livré en sous-assemblages, les grandes configurations du Berri s'assemblent facilement grâce aux vis de serrage situées à chaque extrémité.

CONNECTIONS FACILES
Connectez les modules ou les sous-assemblages du Berri à l'aide de connecteurs électriques.


OPTIONS DE COULEUR
Tubes en aluminium extrudés offerts dans 3 finis : noir texturé, blanc texturé et or doux.

LUMIÈRE DIFFUSE
Deux bandes DEL au centre du diffuseur apportent une lumière diffuse et uniforme.

SPÉCIFICATION PRODUIT	PAR TÊTE			
PERFORMANCE	REG	HO	TUNABLE WHITE REG	TUNABLE WHITE HO
PUISSANCE TOTALE	4.4W	8.1W	4.4W	8W
LUMENS RÉELS (4000K)	671 LM	1143 LM	568 LM	952 LM
EFFICACITÉ	153 LM/W	142 LM/W	129 LM/W	119 LM/W
AUTRE INFORMATION				
POIDS MOY. PAR TÊTE	1.5LBS / 0.7KG	1.5LBS / 0.7KG	1.5LBS / 0.7KG	1.5LBS / 0.7KG
* Se référer aux dessins d'installation pour le poids par configuration.				
L70 (MAINTENANCE DE LA LUMIÈRE)	60,000	60,000	54,700	54,700
CRITÈRES DE CERTIFICATION WELL & LEED				
MAX. LUMINANCE 450-900 NADIR	1150 CD/M² (EN HO)			
MODULE DEL ≥90 IRC	OUI (R9 = 58.8 AVEC 4000K)			
TOLÉRANCE DE CLIGNOTEMENT	PEU DE CLIGNOTEMENT (CONFORME À CALIFORNIA TITLE 24)			

FACTEUR D'EFFICACITÉ

CRI	CCT	FACTOR	TW FACTEUR
80+	5000K	-	0.93
80+	4000K	1.00	1.00
80+	3500K	0.98	0.99
80+	3000K	0.94	0.98
80+	2700K	0.91	0.91
90+	4000K	0.88	-
90+	3500K	0.85	-
90+	3000K	0.81	-
90+	2700K	0.77	-



5 ans de garantie

Visitez notre site Web pour les termes et conditions.